

PA-800 SERIES

Palo Alto Networks PA-800 Series next-generation firewall appliances, comprised of the PA-820 and PA-850, are designed to secure enterprise branch offices and midsized businesses.

Key Security Features:

Classifies all applications, on all ports, all the time

- Identifies the application, regardless of port, encryption (SSL or SSH), or evasive technique employed
- Uses the application, not the port, as the basis for all of your safe enablement policy decisions: allow, deny, schedule, inspect and apply traffic-shaping
- Categorizes unidentified applications for policy control, threat forensics or App-ID™ application identification technology development

Enforces security policies for any user, at any location

- Deploys consistent policies to local and remote users running on the Windows®, Mac® OS X®, Linux®, Android™ or Apple® iOS platforms
- Enables agentless integration with Microsoft® Active Directory® and Terminal Services, LDAP, Novell® eDirectory™ and Citrix®
- Easily integrates your firewall policies with 802.1X wireless, proxies, NAC solutions, and any other source of user identity information

Prevents known and unknown threats

- Blocks a range of known threats, including exploits, malware and spyware, across all ports, regardless of common threat-evasion tactics employed
- Limits the unauthorized transfer of files and sensitive data, and safely enables non-work-related web surfing
- Identifies unknown malware, analyzes it based on hundreds of malicious behaviors, and then automatically creates and delivers protection



PA-800 Series

The controlling element of the Palo Alto Networks® PA-800 Series appliances is PAN-OS® security operating system, which natively classifies all traffic, inclusive of applications, threats and content, and then ties that traffic to the user, regardless of location or device type. The application, content and user – in other words, the business elements that run your business – are then used as the basis of your security policies, resulting in an improved security posture and a reduction in incident response time.

Performance and Capacities ¹	PA-850	PA-820
Firewall throughput (App-ID) ^{2,4}	1.9 Gbps	940 Mbps
Threat prevention throughput ^{3,4}	780 Mbps	610 Mbps
IPsec VPN throughput ^{2,4}	500 Mbps	400 Mbps
New sessions per second ⁵	9,500	8,300
Max sessions	192,000	128,000

¹ Performance and capacities are measured under ideal testing conditions running PAN-OS 8.0

² Firewall and IPsec VPN throughput are measured with App-ID and User-ID features enabled

³ Threat prevention throughput is measured with App-ID, User-ID, IPS, Antivirus and Anti-Spyware features enabled

⁴ Throughput is measured with 64Kb HTTP transactions

⁵ New sessions per second is measured with 4Kb HTTP transactions

PA-800 Series appliances support a wide range of networking features that enable you to more easily integrate our security features into your existing network.

Networking Features

Interface Modes

L2, L3, Tap, Virtual wire (transparent mode)

Routing

OSPFv2/v3 with graceful restart, BGP with graceful restart, RIP, Static routing

Policy-based forwarding

Point-to-Point Protocol over Ethernet (PPPoE)

Multicast: PIM-SM, PIM-SSM, IGMP v1, v2, and v3

Bidirectional Forwarding Detection (BFD)

IPv6

L2, L3, Tap, Virtual wire (transparent mode)

Features: App-ID, User-ID, Content-ID, WildFire and SSL decryption

SLAAC

IPsec VPN

Key exchange: Manual key, IKEv1 and IKEv2 (pre-shared key, certificate-based authentication)

Encryption: 3DES, AES (128-bit, 192-bit, 256-bit)

Authentication: MD5, SHA-1, SHA-256, SHA-384, SHA-512

VLANs

802.1q VLAN tags per device/per interface: 4,094/4,094

Aggregate interfaces (802.3ad), LACP

Network Address Translation (NAT)

NAT modes (IPv4): Static IP, dynamic IP, dynamic IP and port (port address translation)

NAT64, NPTv6

Additional NAT features: Dynamic IP reservation, tunable dynamic IP and port oversubscription

High Availability

Modes: Active/Active, Active/Passive

Failure detection: Path monitoring, interface monitoring

Hardware Specifications

I/O

PA-850 (4) 10/100/1000, (8) Gigabit SFP or
PA-850 (4) 10/100/1000, (4) Gigabit SFP, (4) 10 Gigabit SFP+
PA-820 (4) 10/100/1000, (8) Gigabit SFP

Management I/O

(1) 10/100/1000 out-of-band management port

(2) 10/100/1000 high availability

(1) RJ-45 console port

(1) USB port

(1) Micro USB console port

Storage Capacity

240GB SSD

Power Supply (Average Power Consumption)

PA-850: Two 500W AC power supplies. One power supply is redundant. (75W)

PA-820: 200W power supply. (45W)

Max BTU/hr

256

Input Voltage (Input frequency)

100-240VAC (50-60Hz)

Max Current Consumption

2.0A @ 100VAC, 1.0A @ 240VAC (PA-850)

1.0A @ 100VAC, 0.5A @ 240VAC (PA-820)

Max Inrush Current

1.0A @ 230VAC, 1.84A @ 120VAC (PA-850)

0.4A @ 230VAC, 0.96A @ 120VAC (PA-820)

Rack Mountable (Dimensions)

PA-850 - 1U, 19" standard rack (1.75"H x 14.5"D x 17.125"W)

PA-820 - 1U, 19" standard rack (1.75"H x 14"D x 17.125"W)

Weight (Stand-Alone Device/As Shipped)

PA-850 13.5lbs/21.5 lbs

PA-820 11lbs/18 lbs

Safety

cCSAus, CB

EMI

FCC Class A, CE Class A, VCCI Class A

Certifications

See: <https://www.paloaltonetworks.com/company/certifications.html>

Environment

Operating temperature: 32° to 104° F, 0° to 40° C

Non-operating temperature: -4° to 158° F, -20° to 70° C

Airflow

Front to back

To view additional information about the features and associated capacities of the PA-800 Series, please visit www.paloaltonetworks.com/products.



4401 Great America Parkway
Santa Clara, CA 95054

Main: +1.408.753.4000

Sales: +1.866.320.4788

Support: +1.866.898.9087

www.paloaltonetworks.com

© 2017 Palo Alto Networks, Inc. Palo Alto Networks is a registered trademark of Palo Alto Networks. A list of our trademarks can be found at <http://www.paloaltonetworks.com/company/trademarks.html>. All other marks mentioned herein may be trademarks of their respective companies.
pa-800-series-ds-012617